

Hazardous Polymerization

May Occur

Will Not Occur

Material Safety Data Sheet

Product: Aggre-flex Mesh												
Aggre-flex Mesh Date Issued: 1/2/1993 Revised 1/1/05 Telephone: 800-755-0825 Section 2 - Hazard Ingredients/Identity Information Ingredients CAS# OSHA-PEL ACGIH-TLV % Fibrous glass Dust 65997-17-3 15 mg/cuM 10 mg/cuM - All meshes are coated with water-based synthetic polymers and resins. Exposure to these polymers and resins is not a hazard from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: N/A Specific Gravity (H ₂ O=1):	Section 1 - Material Identification											
Telephone: 800-755-0825	Product:				Manufacturer:	Master V	/all Inc.					
Telephone: 800-755-0825		Aggre-flex	Mesh		Address:	6975 Flat	Rock Road					
Telephone: 800-755-0825 Section 2 - Hazard Ingredients/Identity Information		, 199.0			rtadrooc.							
Section 2 - Hazard Ingredients/Identity Information Ingredients	Date Issued:	1/2/1993 Rev	rised 1/1/05			,	071 01020					
Ingredients	Date located. II II 1000 Revised II II II II				Telephone:	800-755-	0825					
Fibrous glass Dust 65997-17-3 15 mg/cuM 10 mg/cuM - All meshes are coated with water-based synthetic polymers and resins. Exposure to these polymers and resins is not a hazard from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Not is appropriate for surrounding fire Use what is appropriate for surrounding fire Special Fire Fighting Procedures: Incombustible Fiammable Limits: N/A LEL N/A UEL N/A Use what is appropriate for surrounding fire Use what is appropriate for or polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Conditions to Avoid: Incompatibility (Materials to Avoid):	Section 2 - Hazard Ingredients/Identity Information											
Fibrous glass Dust 65997-17-3 15 mg/cuM 10 mg/cuM - All meshes are coated with water-based synthetic polymers and resins. Exposure to these polymers and resins is not a hazard from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Pressure: Vapor Pressure: Vapor Pressure: Vapor Unstable Evaporation Rate (Butyl Acetate=1): Insoluble No discernable odor Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Use what is appropriate for surrounding fire Use what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):	Ingredients	CAS#		OSHA-PEL		ACGIH-	TLV		%			
All meshes are coated with water-based synthetic polymers and resins. Exposure to these polymers and resins is not a hazard from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: No discernable odor Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Use what is appropriate for surrounding fire Themail decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):												
from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stable X Incompatibility (Materials to Avoid):		65997-17-3		15 mg/cuM		10 mg/cuM -			-			
from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stable X Incompatibility (Materials to Avoid):												
from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stable X Incompatibility (Materials to Avoid):												
from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stable X Incompatibility (Materials to Avoid):												
from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stable X Incompatibility (Materials to Avoid):												
from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less. Respirable fibrous glass dust of 3.5-micron diameter or less is not likely to result from normal cutting operations on these fabrics. Section 3 - Physical/Chemical Characteristics Boiling Point: Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):												
Section 3 - Physical/Chemical Characteristics Boiling Point:	from this product. Occupational exposure limits for respirable fibrous glass dust are listed. Respirable fibrous glass is considered to be glass fibers with a diameter of 3.5 microns or less.											
Boiling Point: N/A Specific Gravity (H ₂ O=1): 2.5 Vapor Pressure: N/A Melting Point: Fiberglass 1400°C Vapor Density (AIR=1): Evaporation Rate (Butyl Acetate=1): Solubility in Water: Appearance and Odor: No discernable odor Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Incombustible Flammable Limits: N/A LEL N/A UEL N/A Extinguishing Media: Use what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):	1. 1000 in the state of the sta											
Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Flash Point (Method Used) Extinguishing Media: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Use what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):			Section	n 3 - Physical/Chem	ical Characte	ristics						
Vapor Pressure: Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Flash Point (Method Used) Extinguishing Media: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Use what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):	Dailing Daint		NI/A	Crocific Crovity	(11.0.4):		0.5					
Vapor Density (AIR=1): Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Evaporation Rate (Butyl Acetate=1): Insoluble No discernable odor Section 4 - Fire and Explosion Hazard Data Incombustible Flammable Limits: N/A LEL N/A UEL N/A Use what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable x Incompatibility (Materials to Avoid):	_							10000				
Solubility in Water: Appearance and Odor: Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Insoluble No discernable odor Section 4 - Fire and Explosion Hazard Data Incombustible Flammable Limits: N/A UEL N/A USe what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):		0_1\.	IN/A					1400 C				
Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid): Section 4 - Fire and Explosion Hazard Data Incombustible Flammable Limits: N/A LEL N/A UEL N/A Use what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data												
Section 4 - Fire and Explosion Hazard Data Flash Point (Method Used) Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid): Section 4 - Fire and Explosion Hazard Data Flammable Limits: N/A LEL N/A UEL N/A UEL N/A UEL N/A UEL N/A UEL N/A UEL N/A UHA UEL N/A UEL	•											
Flash Point (Method Used) Extinguishing Media: Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Conditions to Avoid: Stable X Incombustible Flammable Limits: N/A LEL N/A UEL N/A Incompatibility (Materials to Avoid):	TAPPORTATION CITY CHOCKET THE PROPERTY OF THE											
Extinguishing Media: Use what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):	Section 4 - Fire and Explosion Hazard Data											
Extinguishing Media: Use what is appropriate for surrounding fire Thermal decomposition of polymers and resins in coating may produce irritating fumes. Firefighters should wear full protective gear. Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid):	Flash Point (Method Used) Incombus			le Flammable Limits:	N/A	LEL	N/A	UEL	N/A			
Special Fire Fighting Procedures: Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid): Incompatibility (Materials to Avoid):	· · · · · · · · · · · · · · · · · · ·		Use what is									
Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data Stability Unstable Stable X Incompatibility (Materials to Avoid): Although treated for non-combustibility, under extreme conditions polymers may burn or flash. Conditions to Avoid: X Incompatibility (Materials to Avoid):												
Unusual Fire and Explosion Hazards: Section 5 - Reactivity Data	Special Fire Fighting Procedures: fumes. Firefighters should wear full protective gear.											
Section 5 - Reactivity Data Stability Unstable Conditions to Avoid: Incompatibility (Materials to Avoid):												
Stability Unstable Conditions to Avoid: Incompatibility (Materials to Avoid):	Unusual Fire and Explosion Hazards: burn or flash.											
Stability Unstable Conditions to Avoid: Incompatibility (Materials to Avoid):				Section 5 - Reac	tivitv Data							
Stable x Incompatibility (Materials to Avoid):	Otal III.	Hantal I.		1								
Incompatibility (Materials to Avoid):	Stability			Conditions to Avoid:								
	Incompatibility (Ma											

Conditions to Avoid:



Material Safety Data Sheet

Aggre-flex Mesh

Section 6 - Health Hazard Data										
Routes of Entry Health Hazards (Ac	Inhalation? Yes ute and Chronic) rous glass as a nuisance dust	Skin? Yes		Ingestion? N/A						
COLITY GIGGOINGS HE	out glace as a haloante duct									
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?							
No										
Signs and Symptom	ns of Exposure: and respiratory tract irritation									
-										
Medical Conditions Generally Aggravated by Exposure Respiratory ailments - as with any nuisance dust upon prolonged and repeated exposure.										
	A Ald Durandous									
Emergency and First Eye contact: flush was to fresh air		nedical assistance if irritation persists.	Skin: wash with soap and w	/ater. Inhalation: remove						
Section 7 - Precautions for Safe Handling and Use										
	Section 7	- Precautions for Safe Handi	ing and Use							
Steps to be taken in case material is released or spilled Prevent spread of fiberglass dust and avoid dust generating conditions. Those involved in clean up of particles should use appropriate personal protective equipment.										
appropriate perso	nai protoctivo oquipinonti									
Waste Disposal Method										
In most cases, woven fiberglass scrap can be disposed of in a sanitary landfill in accordance with federal state and local regulations. Check with local authorities.										
Precautions to be	taken in handling and storin	g								
Store and use in a manner that will prevent airborne particles in the workplace.										
Other Precautions										
None known										
Section 8 - Control Measures										
Respiratory Prote	ction (Specify Type)									
Where dust levels exceed the TLV, use OSHA approved dust respirator										
Ventilation	Local Exhaust	Where dust generation is appare	ent Special	Not normally required						
	Mechanical (General)	Where local exhaust is not feasi	ble Other	Not normally required						
Protective Gloves	: If necessary	Eye Protec	ction: Safety gla	asses or goggles						
Other Protective (Clothing or Equipment									
Work aprons or s										
Work/Hygienic Pr	actices									
		ering of work clothing is recommen	ded.							

EPA Supplier Notification/Environmental:

This trade name product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Re-authorization Act of 1986 (SARA) and 40 CFR Part 372.

This product contains no ingredients on the list of Extremely Hazardous Substances for SARA Emergency Planning. Tier I / Tier II Hazard Category (40 CFR 370): Immediate Health Hazard.

The information contained in this bulletin is based upon data considered accurate and is presented in good faith. Master Wall Inc. assumes no liability, either expressed or implied for personal injury or any other conditions caused by the use of this material.